



SIMATIC S7-300, DIGITAL INPUT SM 321,
OPTICALLY ISOLATED 16DI, 24 V DC,
SOURCE INPUT, 1 X 20 PIN

Supply voltage

Load voltage L+

Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V

Input current

from backplane bus 5 V DC, max.	10 mA
---------------------------------	-------

Power losses

Power loss, typ.	3.5 W
------------------	-------

Digital inputs

Number/binary inputs	16
Input characteristic curve acc. to IEC 61131, Type 1	Yes

Number of simultaneously controllable inputs

horizontal installation

up to 40 °C, max.	16
up to 60 °C, max.	16

vertical installation

up to 40 °C, max.	16
-------------------	----

Input voltage	
Type of input voltage	DC
Rated value, DC	24 V
for signal "0"	-5 to +30 V
for signal "1"	-13 to -30 V
Input current	
for signal "1", typ.	7 mA
Input delay (for rated value of input voltage)	
for standard inputs	
Parameterizable	No
at "0" to "1", min.	1.2 ms
at "0" to "1", max.	4.8 ms
Cable length	
Cable length, shielded, max.	1000 m
Cable length unshielded, max.	600 m
Encoder	
Connectable encoders	
2-wire sensor	Yes
Permissible quiescent current (2-wire sensor), max.	1.5 mA
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	No
Interrupts/diagnostics/status information	
Alarms	
Alarms	No
Diagnostic alarm	No
Hardware interrupt	No
Diagnostic messages	
Diagnostic functions	No
Diagnostics indication LED	
Status indicator digital input (green)	Yes
Galvanic isolation	
Galvanic isolation digital inputs	
between the channels	No
between the channels, in groups of	16
between the channels and the backplane bus	Yes ; Optocoupler
Permissible potential difference	
between different circuits	75 VDC / 60 VAC

Isolation	
Isolation checked with	500 V DC
Connection method	
required front connector	20-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weight	
Weight, approx.	200 g

Status

Feb 27, 2013